


## Conclusion

Please direct any questions or comments to Joseph M. Homa at (607) 974-9061.

Respectfully submitted,

CORNING INCORPORATED

Date: 5/9/02

  
\_\_\_\_\_  
Joseph M. Homa  
Registration No. 40,023  
Corning Incorporated  
Patent Department  
Mail Stop SP-TI-03-1  
Corning, NY 14831

**CERTIFICATE OF MAILING UNDER 37 C.F.R. § 1.8:** I hereby  
certify that this correspondence is being deposited with the United States  
Postal Service as first class mail in an envelope addressed to Asst.  
Commissioner of Patents and Trademarks, Washington, D.C. 20231 on  
5/9/02  
Date of Deposit

\_\_\_\_\_  
Joseph M. Homa  
Name of applicant, assignee, or  
Registered Representative

  
\_\_\_\_\_  
Signature

5/9/02  
Date of Signature

MAY 17 2002

VERSION WITH MARKINGS TO SHOW CHANGES MADE

RECEIVED

MAY 22 2002

TC 2800 MAIL ROOM

36. (Canceled without prejudice) An optical waveguide fiber comprising:
- a core region having a centerline and at least two segments having a positive relative refractive index, a refractive index profile, and an inner and an outer radius, the radii being measured with reference to the centerline;
  - a clad layer surrounding and in contact with the core region, the clad layer having a relative index and a refractive index profile;
  - wherein the optical waveguide fiber exhibits an optical attenuation at a wavelength of about 1383 nm which is not more than 0.10 dB/km above an optical attenuation exhibited at a wavelength of about 1310 nm.
37. (Canceled without prejudice) An optical waveguide fiber comprising:
- a silica containing glass core; and
  - a glass cladding surrounding the silica containing glass core;
  - wherein the optical waveguide fiber exhibits an optical attenuation at a wavelength of about 1383 nm which is not more than 0.10 dB/km above an optical attenuation exhibited at a wavelength of about 1310 nm; and
  - wherein the optical waveguide fiber exhibits a zero dispersion at a wavelength greater than 1310 nm.